

PRODUCT CATALOG







This catalog contains all of Cold Jet's i³ MicroClean® product offerings and all part numbers that were current at the time of catalog production.

Images shown are for representative purposes only.

Products may vary from the images displayed. Cold Jet will always ship the latest version of each part. Invoices will always reflect the latest revision level numbers.

Cold Jet is not liable for typographical errors or changes to specifications presented.

Check www.coldjet.com for the most recent version of this document.

Contact your Cold Jet representative for the most current information.

Business Hours:

Monday - Friday 8:30 am - 5 pm local time

Business Offices		Customer Service	
USA:	+1 513.831.3211 +1 800.337 9423 info@coldjet.com	USA (24 Hours)	+1 800 777.9101 service@coldjet.com
Canada:	+1 800.337.9423 x 501	Canada Business Hours: After Hours:	+1 800.337.9423 x 501 +1 800 777.9101
Germany:	+49 (0)6551 9606.0	Germany Business Hours: After Hours:	+49 (0)6551 9606.0 +1 513 576.8981
Europe:	+32 (0)13 53 95 47 info.eu@coldjet.com	Europe/Belgium Business Hours: After Hours:	+32 (0)13 53 95 47 +1 513 576.8981 service.eu@coldjet.com
Latin America:	+52 (81)10 97 0445	Latin America Business Hours: After Hours:	+52 (81)10 97 0445 +1 513 576.8981
Middle East:	+32 (0)13 53 95 47	Middle East Business Hours: After Hours:	+32 (0)13 53 95 47 +1 513 576.8981
Asia:	+81 3 4360 8200		

©Copyright Cold Jet, LLC 2010 (08.19.2011)

"Cold Jet" and "i³ MicroClean" are registered trademarks of Cold Jet, LLC





This unique cleaning system capitalizes on Cold Jet's patented shaved ice and feeder technologies to deliver a complete precision cleaning solution. It is an ergonomic and intuitive system that utilizes a readily available blast medium, and is fast, effective and proven reliable. Its unparalleled low air and ice consumption provides cost-effective operation in an almost noise-free environment.

The i³ MicroClean system includes:

- i³ MicroClean blast machine
- One length of dry ice blast hose
- One length of air hose
- Applicator
- Customer-specified nozzles
 (MC35 where none is specified)
- Transport cart

Handles Block Sizes:
6" x 6" x 12"
(150 mm x 150 mm x 300 mm)
or
5" x 5" x 10"
(127 mm x 127 mm x 254 mm)
(with available insert)



SPECIFICATIONS

Air supply pressure range 50 to 140 psi (3.4 to 9.7 bar)

(200-240 VAC, 1 Ø 50/60 Hz, 5 amps)

Internal air filter designed to remove water, oil, rust and other articles from the air supply 12-month warranty (extended warranty packages available)



Standard Blast Applicator

Our lightweight, ergonomic design with high visibility lighting enabling blasting at various angles and in any environment. High intensity LED lights on applicator face light up dark surfaces being cleaned. Includes air-only feature and safety switch.

Part #: 2E0492 - Applicator



Full-pressure precision blast nozzles.

Air consumption rates indicated are based on standard 80 psi (5.5 bar) blast pressure.



12 CFM (0.3 m³/min) Yellow color Blast swath 0.13" (3.2 mm) 6" (15 cm) length

Part #: 13865-126

25 CFM (0.7 m³/min) White color Blast swath 0.19" (4.7 mm) 6" (15 cm) length

Part #: 13865-256

50 CFM (1.5 m³/min) Blue color Blast swath 0.31" (7.9 mm) 6" (15 cm) length

Part #: 13865-506



Advanced Nozzles

Nozzles using advanced MERN technology for superior performance.

35 CFM (1.0 m³/min) MERN Blast swath 0.26" (6.6 mm) 5" (12.7 cm) length

Part #: 5E0284 (MC26M)

50 CFM (1.5 m³/min) MERN Blast swath 0.29" (7.4 mm) 6" (15 cm) length

Part #: 5E0248 (MC29MH)





25 CFM (0.7 m³/min) Fan Blast swath 0.35" (8.9 mm) 6" (15 cm) length

Part #: 5E0219 (MC35)

25 CFM (0.7 m³/min) Fan Blast swath 0.47" (11.9 mm) 6" (15 cm) length

Part #: 5E0220 (MC47)

30 CFM (0.9 m³/min) Fan Blast swath 0.88 in (22 mm) 5" (12.7 cm) length

Part #: 5E0241 (MC88)

25 CFM (0.7 $\rm m^3/min$) Fragmenting Fan Blast swath 0.88" (22 $\rm mm$) 5" (12.7 $\rm cm$) length

Part #: 5E0254 (MC88F)



Angled Nozzles
Recommended for use with 0.38" (0.97 cm) Rotary
Union Part #: 2N0189

45° Angled Nozzle Blast swath 0.25" (6 mm) 1" (2.54 cm) cavity opening 6" (15 cm) length

Part #: 5E0223 (MC25A45)

90° Angled Nozzle Blast swath 0.25" (6 mm) 1" (2.54 cm) cavity opening 6" (15 cm) length

Part #: 5E0227 (MC25A90)









Nozzle Accessories

Extension Tubes

- Used to extend nozzles
- · Connects directly to nozzle and applicator
- Available in three lengths:
 - 5" (12.7 cm)
 - 10" (25.4 cm)
 - 15" (38.1 cm)

Part #: 3E0974-Length



Rotary Union

- Used to rotate nozzles
- 3/8" (9.5 mm) JICF to JICM
- Lightweight
- Hard-coat anodized Aluminum

Part #: 2N0189



Hoses

Blast Hose Assembly*

3/8" (9.5 mm), 12' (3.7 m) proprietary blast hose section with control cable and bonding cable.

Part #: 2N0220-G2



Flexible silicone blast hose with control cable and bonding cable.

Part #: 2N0217



One shaft collar is required per hose run.

Part #: 3N0086 (13/16" bore for 3/8" hose)



Air Hose

1/2" (12.7 mm) ID, 25' (7.6 m) length. Used to carry pressurized air from air source to blast unit. Includes quick disconnects.

Part #: 2N0184



Accessories

Block Handler

Allows for easy handling of Dry Ice Block.

Part #: 70540-001



Mobility/Storage Cart

Basic Mobility Cart and Ice Storage Cooler

Basic frame cart for transport, comes standard with machine and includes ice storage cooler.

Part #: 2Z0013 (shown)

Replacement ice cooler lce Storage cooler only.

Part #: 3Z0083



Safety Accessories

Safety Kit

- Meets United States Occupational Safety & Health Association (OSHA) requirements for operator noise protection (with the use of properly rated and worn ear plugs).
- Kit includes the following:
 - 100 sets of ear plugs
 - 2 ear protectors
 - Eye protector shield
 - Gloves
 - Block handler

Part #: 2Z0001-1 - Safety Kit with Block handler

Foot Switch

Eliminates the need for handheld control switch. Allows nozzle to be attached directly to the blast hose for better ergonomics. "Deadman style" safety foot pedal.

Part #: 2G1299



