

DRY ICE BLASTING REINVENTED

# PCS®60





THE NEW STANDARD
IN DRY ICE BLASTING

### MACHINE DIMENSIONS

Length x Width x Height: 39 in (99 cm) x 19 in (48 cm) x 45 in (114 cm) Weight: 269 lb (122 kg)

### **POWER REQUIREMENTS**

110/220V AC (50/60 Hz)

Compliant with the EU Machinery Directive (CE) and UL Design Standards

### HOPPER CAPACITY

60 lb (27 kg)

### **HMI DISPLAY**

7" LCD Color Screen

### **FEED RATE**

Variable - up to 4 lb/min (1.8 kg/min)

### **PARTICLE CONTROL SYSTEM**

Variable Dry Ice Size: 3mm - 0.3mm Utilizes 28 distinct dry ice particle sizes

### **BLAST PRESSURE RANGE**

20 - 145 psi (1.4 - 10 bar)

### **COMPRESSED AIR SUPPLY**

40 - 145 psi (2.8 - 10 bar)

### **NOZZLE AIR CONSUMPTION**

 $12 - 100 \text{ cfm } (0.3 - 2.8 \text{ m}^3/\text{min})$  at 80 psi (5.5 bar)

### **BLAST FLOW PATH**

3/4" Straight Through Tubing

### **SUREFLOW**

Thumper, Ramrods, Electric Vibrator "Always-On" Hopper Agitation



### DRY ICE BLASTING REINVENTED

### **VERSATILE**



Revolutionary and patented Particle Control System<sup>™</sup> (PCS)

Precisely cut dry ice particles from 3mm to 0.3mm and every size in between



## EASY TO USE



7" LCD screen with digital controls

Intuitive HMI display - Easily view and control blasting parameters and machine settings

Programmable and password-protected application recipes (blast pressure, particle size, feed rate)

### **FASTER**



Advanced Aerodynamic Low Load Airlock Feeder leads to consistent and pulse-free blast stream, enabling impactful cost savings

### **SMART**



### Cold Jet, CONNECT®

Remote monitoring and diagnostics with industry-first Cold Jet CONNECT

Proactive customer service keeps PCS 60 up and running at all times



INTEGRATION READY

Ready to connect to a robot or any other PLC-controlled automation system via optional accessory package

### **EFFICIENT**



Streamlined "straight-through" air system maximizes air supply yield

Patented High-Efficiency Flow Initiation Regulator

Patented Advanced Direct Drive Feeding System

DURABLE

Coated tool grade aluminum alloy,

stainless steel and polymer frame

Engineered to minimize part wear

### **ERGONOMIC**



Optimized design and combination of materials leads to weight and size reduction

Wheels and braking system are designed for mobility and maneuverability

> Redesigned blast hoses for flexibility and durability

### QUIET



Cleans effectively at lower air supply and blast pressures

Proprietary enclosed thumper system

## WHAT'S INCLUDED?

Free 2-year trial subscription of Cold Jet CONNECT + your choice of the Performance Kit or Precision Kit

### **PERFORMANCE KIT**

3/4" or 1" PERFORMANCE APPLICATOR CHOICE OF PERFORMANCE NOZZLE

**NOZZLE HANDLE** 

1" AIR SUPPLY HOSE

3/4" or 1" HYBRID-FLEX BLAST HOSE

HOSE CARRIER

HOSE WRAP

### **PRECISION KIT**

1/2" PRECISION APPLICATOR

CHOICE OF 2 PRECISION NOZZLES

1" AIR SUPPLY HOSE

1/2" HYBRID-FLEX BLAST HOSE

**HOSE CARRIER** 

HOSE WRAP



